

## Specifications\*

MODEL		SX25
<b>ENGINE (DIESEL)</b>		
Model		Shibaura S773L-EU
Typ		3-cylinder water-cooled diesel engine
Displacement	cc	1131
Gross power	SAE hp/ (kW) / DIN hp/ (kW)	30.0 (22.5) / 26.0 (19.4)
Torque	Nm @ rpm.	67.0 @ 2400
Rated speed	rpm.	3000
Fuel tank capacity	l.	26
<b>TRANSMISSION</b>		
Transmission		Hydrostatic
Range		V/R 2
Driving speed	Forward	0 - 17.0
	Reverse	0 - 11.5
4-wheel drive		mechanical
Differential lock		mechanical
Brake		wet disc
<b>TIRES</b>		
Industrial/ terra	Front	18x8,50-8 R4
	Rear	26x12,00-12 R4
Turf	Front	18x8,50-8 R3
	Rear	26x12,00-12 R3
<b>PTO</b>		
Power	hp	20.5
Rear	l/min.	540
Mid	l/min.	2000
Rear		option
<b>HYDRAULIC SYSTEM</b>		
Pump capacity	l/min.	24.6
Steering		Hydraulic power steering
Control valve		option: 1 x double acting rear
3-point hitch		Category I
Max. lifting capacity	kg	715
<b>DIMENSIONS</b>		
Length	mm	2445
Width	mm	1180
Height	mm	2280
Ground clearance	mm	185
Wheel base	mm	1400
Weight inkl. ROPS	(kg)	696

\*We reserve the right to discontinue models or change specifications without notice.

### Important information

• Improper use of any product may cause serious or fatal injury. Read carefully the operating and safety instructions in your owners manual before use.

# SHIBAURA

**SHIBAURA EUROPE BV**

Begonialaan 7

NL - 6851 TE Huissen

T. 0031 (0)26 326 9999

F. 0031 (0)26 326 9990

E. [info@shibaura.com](mailto:info@shibaura.com)

I. [www.shibaura.com](http://www.shibaura.com)

Dealer: