

## Specifications \*

Tractor model		ST330	ST333
Drive		4WD	
Transmission type		MECH	
<b>Engine</b>			
Model		N843	
Type		Watercooled, 3-cylinder Shibaura Diesel	
Gross horsepower	(SAE hp (kW))/ (DIN hp (kW))	34,5 (25,8) / 30 (22,4)	37,9 (28,3) / 33 (24,6)
Displacement	(cc)	1496	
Rated speed	(rpm)	2800	
Battery	(V-A)	12 - 55	
Alternator	(A)	40	
Fuel tank capacity	(l)	29,5	
<b>PTO</b>			
Type		One way clutch/ Live	
Rear PTO power	(hp/ (kW))	23,7 (17,7)	26 (19,4)
Rear PTO rated speed	(rpm)	616	
Mid PTO rated speed	(rpm)	2358	
<b>Hydraulic</b>			
Lift control type: position		Standard	
Max. lifting capacity	(kg)	1400	
3-point hitch		Category I	
<b>Traveling System</b>			
Steering		Power steering	
Brake		Wet disk	
Clutch		Dry, Single	
<b>Standard tyres</b>			
Agricultural	Front	6x14	
	Rear	9,5x24	
Turf	Front	25x8,50-14	
	Rear	13,6x16	
<b>Ground Speed at engine rated speed</b>			
MECH (9x3)	Front	(km/h)	1,3 - 21,4
	Rear	(km/h)	1,8 - 14,9
<b>Dimensions (AG. tyres &amp; ROPS)</b>			
Overall length		(mm)	2825
Overall width		(mm)	1345
Overall height		(mm)	2490
Wheelbase		(mm)	1600
Ground clearance		(mm)	285
Tread	Front	(mm)	1100
	Rear	(mm)	1070
Weight		(kg)	1115



### Important information

• Improper use of any product may cause serious or fatal injury. Read, understand and follow carefully the operating and safety instructions in your owner's manual before using such products.

\* Specifications and design subject to change without notice.

# SHIBAURA

**SHIBAURA EUROPE BV**

Begonialaan 7

NL - 6851 TE Huissen

Tel. (0031) 026 326 9999

Fax (0031) 026 326 9990

E-mail: [info@shibaura.com](mailto:info@shibaura.com)

[www.shibaura.com](http://www.shibaura.com)

Dealer: